

## AXW SERIES

## ◆ FEATURES

- Load Life : 105°C 2000 hours.
- Body diameter of  $\phi 10\text{mm}$  to  $\phi 18\text{mm}$  with high ripple current capability.
- This series is two classes smaller than the current MXW series.
- RoHS compliance.



## ◆ SPECIFICATIONS

Items	Characteristics									
Category Temperature Range	$-25 \sim +105^\circ\text{C}$									
Rated Voltage Range	200 ~ 450V.DC									
Capacitance Tolerance	$\pm 20\%$ (20°C, 120Hz)									
Leakage Current(MAX)	$I=3\sqrt{CV}$ (After 5 minutes application of rated voltage) I=Leakage Current( $\mu\text{A}$ )      C=Rated Capacitance( $\mu\text{F}$ )      V=Rated Voltage(V)									
Dissipation Factor(MAX) ( $\tan\delta$ )	Rated Voltage (V)	200 ~ 250	400	420 ~ 450						
	$\tan\delta$	0.12	0.15	0.2						
Endurance	After applying rated voltage with rated ripple current for 2000hrs at 105°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within <math>\pm 20\%</math> of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>				Capacitance Change	Within $\pm 20\%$ of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.
Capacitance Change	Within $\pm 20\%$ of the initial value.									
Dissipation Factor	Not more than 200% of the specified value.									
Leakage Current	Not more than the specified value.									
Impedance Ratio(MAX)	Rated Voltage (V)	200 ~ 250	400 ~ 450	(120Hz)						
	$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$	3	8							

## ◆ MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency (Hz)	60(50)	120	500	1k	10k $\leq$
Coefficient	200 ~ 250WV	0.8	1.0	1.20	1.30
	400 ~ 450WV	0.8	1.0	1.25	1.40

## ◆ PART NUMBER

   AXW  
 Rated Voltage    Series             
 Option    Lead Forming    D x L    Case Size



## MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

AXW

## ◆ DIMENSIONS

(mm)

φD	10	12.5	14.5	16	18
φd	0.6		0.8		
F	5.0		7.5		
α		2.0			

## ◆ STANDARD SIZE, RATED RIPPLE CURRENT

Cap (μF)	WV	200					220						
		φ10	φ12.5	φ14.5	φ16	φ18	φ10	φ12.5	φ14.5	φ16	φ18		
56							10x30	0.29					
68	10x30	0.35					10x35	0.33					
82	10x35	0.40					10x40	0.37					
100	10x40	0.46						12.5x30	0.43				
120			12.5x30	0.53				12.5x35	0.49				
150			12.5x35	0.62				12.5x40	0.58	14.5x30	0.58		
180			12.5x40	0.70	14.5x30	0.66				14.5x35	0.68		
220				14.5x35	0.80	16x30	0.76	18x30	0.81		16x30	0.67	
270				14.5x40	0.90	16x35	0.88	18x30	0.87		14.5x40	0.78	
330					16x40	1.10	18x35	1.01				16x5	0.77
390						18x40	1.13					18x30	0.77
470						18x45	1.27					18x40	1.01
												18x45	1.13

Cap (μF)	WV	250					400						
		φ10	φ12.5	φ14.5	φ16	φ18	φ10	φ12.5	φ14.5	φ16	φ18		
22							10x30	0.21					
27							10x35	0.24					
33							10x40	0.28					
39								12.5x30	0.32				
47	10x30	0.27						12.5x35	0.37				
56	10x35	0.30						12.5x40	0.42	14.5x30	0.42		
68	10x40	0.35							14.5x35	0.48			
82		12.5x30	0.40						14.5x35	0.52	16x30	0.50	
100		12.5x35	0.46							16x35	0.58		
120		12.5x40	0.53	14.5x30	0.53					16x40	0.66		
150			14.5x35	0.62	16x30	0.62					18x40	0.77	
180			14.5x40	0.72	16x35	0.72	18x30	0.72				18x45	0.88
220				16x40	0.83	18x35	0.83						
270					18x40	0.95							
330					18x45	1.07							

Cap (μF)	WV	420					450					
		φ10	φ12.5	φ14.5	φ16	φ18	φ10	φ12.5	φ14.5	φ16	φ18	
15							10x30	0.15				
18	10x30	0.17					10x35	0.18				
22	10x35	0.20					10x40	0.21				
27	10x40	0.23						12.5x30	0.25			
33		12.5x30	0.27					12.5x35	0.28			
39		12.5x35	0.31					12.5x40	0.32	14.5x30	0.32	
47		12.5x40	0.36	14.5x30	0.36				14.5x35	0.38	16x30	0.38
56			14.5x35	0.43	16x30	0.43			14.5x40	0.44	16x35	0.44
68			14.5x40	0.51	16x35	0.51	18x30	0.51			16x40	0.49
82				16x40	0.57	18x30	0.57				18x35	0.55
100					18x35	0.61					18x40	0.65
120					18x40	0.66					18x45	0.74

Please check with us about individual WV, Cap., size and dimensions.

Size φD × L(mm)

Ripple Current (A r.m.s./105°C, 120Hz)